

LUCTRA® VITAWORK® HCL 12 Asym. PIR (Art.-Nr.: 9283-140)



LED luminaire with table clamp for visual comfort (ergonomic LED free-standing luminaire), double asymmetrical, direct / indirect distribution

LED free-standing luminaire direct/indirect distribution, asymmetrical, luminaire head direct: with asymmetrical light guiding panel / indirect with clear diffuser; asymmetrical light distribution for illuminating deep rooms.

Illuminants: LED; luminous flux approx 11,145 lm, power consumption approx 86 W, effective light output >135 lm/W, 2,700 K – 6,500 K, colour rendering CRI ≥ 80; colour tolerance SDCM <3; UGR <16, energy efficiency class: A++; lifetime (L85B10) > 50,000 hours; power supply length 3 m and Schuko-Plug; Stand-by consumption ≤ 0.5W.

Operation: direct and indirect components separately and continuously dimmable via the capacitive touch control panel with patented VITACORE® electronics, with switchable infrared presence and light intensity sensors, optimised for height-adjustable desks. Seamless adjustment of the colour temperature. Attachment by table clamp with a clamping range of 16-60 mm.

Luminaire head aligned transversely to mast (WxDxHxD) 542 x 370 x 32.5 mm, head surface: metallic silver, side parts: black; mast made of aluminium, mast surface: metallic silver, front cover: black, dimensions H 1,395 mm; clear height > 2m

CE, protection class I, protection class IP20

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Germany

Phone +49 2371 662-445

info@luctra.de · www.luctra.eu

LUCTRA® VITAWORK® HCL 12 Asym. PIR (Art.-Nr.: 9281-140)



LED free-standing luminaire for visual comfort (ergonomic LED free-standing luminaire), double asymmetrical, direct / indirect distribution

LED free-standing luminaire direct/indirect distribution, asymmetrical, luminaire head direct: with asymmetrical light guiding panel / indirect with clear diffuser; asymmetrical light distribution for illuminating deep rooms.

Illuminants: LED; luminous flux approx 11,145 lm, power consumption approx 86 W, effective light output >135 lm/W, 2,700 K – 6,500 K, colour rendering CRI ≥ 80; colour tolerance SDCM <3; UGR <16, energy efficiency class: A++; lifetime (L85B10) > 50,000 hours; power supply length 3 m and kettle plug; Stand-by consumption ≤ 0.5W.

Operation: direct and indirect components separately and continuously dimmable via the capacitive touch control panel with patented VITACORE® electronics, with switchable infrared presence and light intensity sensors, optimised for height-adjustable desks. Seamless adjustment of the colour temperature.

Luminaire head aligned transversely to mast (WxDxHxD) 542 x 370 x 32.5 mm, head surface: metallic silver, side parts: black; mast made of aluminium, mast surface: metallic silver, front cover: black, base C-shaped made of steel, base surface: metallic silver; dimensions: H 2,040 mm; clear height > 2m

CE, protection class I, protection class IP20

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Germany

Phone +49 2371 662-445

info@luctra.de · www.luctra.eu

LUCTRA® VITAWORK® HCL 12 Asym. DIM (Art.-Nr.: 9282-140)



LED free-standing luminaire for visual comfort (ergonomic LED free-standing luminaire), double asymmetrical, direct / indirect distribution

LED free-standing luminaire direct/indirect distribution, asymmetrical, luminaire head direct: with asymmetrical light guiding panel / indirect with clear diffuser; asymmetrical light distribution for illuminating deep rooms.

Illuminants: LED; luminous flux approx 11,145 lm, power consumption approx 86 W, effective light output >135 lm/W, 2,700 K – 6,500 K, colour rendering CRI ≥ 80; colour tolerance SDCM <3; UGR <16, energy efficiency class: A++; lifetime (L85B10) > 50,000 hours; power supply length 3 m and kettle plug; Stand-by consumption ≤ 0.5W.

Operation: direct and indirect components separately and continuously dimmable via the capacitive touch control panel with patented VITACORE® electronics, optimised for height-adjustable desks. Seamless adjustment of the colour temperature.

Luminaire head aligned transversely to mast (WxDxHxD) 542 x 370 x 32.5 mm, head surface: metallic silver, side parts: black; mast made of aluminium, mast surface: metallic silver, front cover: black, base C-shaped made of steel, base surface: metallic silver; dimensions: H 2,040 mm; clear height > 2m

CE, protection class I, protection class IP20

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Germany

Phone +49 2371 662-445

info@luctra.de · www.luctra.eu