

VITAWORK®



Fact Sheet

TECHNICAL DATA

VITAWORK® 7			
Colours	140 Metallic Silver/Black (similar RAL 9006 / 7021)		
Dimensions	Height:	2,040 mm	
	Luminaire head (W x D x H):	542 x 370 x 32,5 mm	
	Ceiling height clearance:	> 2 m	
Weight	19 kg		
Lamp base	C-shaped		
Material	Aluminium, Steel (lamp base), Plastic (touch panel & side caps)		
Energy efficiency	This product contains (a) light source(es) with the energy efficiency class(es)		
	Light source direct no. 34601, energy efficiency class D (Reg. 908500)		
	Light source indirect no. 34600, energy efficiency class D (Reg. 908623)		
Protection type	IP 20		
Protection class	I ⚡		
Illuminants			
Fitted with	LED		
Power consumption	52 W		
Light distribution	symmetric		
Nominal luminous flux direct	2,000 lm		
Nominal luminous flux indirect	5,000 lm		
Nominal luminous flux	7,000 lm		
Luminous efficiency	>131 lm/W		
Colour temperature (CCT)	4.000 K		
Colour tolerance	< 3 SDCM		
50,000 h	L85B10		
UGR	< 16		
Colour reproduction index	> 80		
Plug	Schuko-plug (Type F) / Kettle plug + EU/CH/UK - plug		
Cable length	3 m		
Standby consumption	≤ 0,5 W		
VITACORE®			
Operation	via VITACORE® electronics and sensors		
Light intensity setting	Seamless and in five steps direct & indirect dimming via the touch panel		
Sensors	Infrared Presence Sensor & Luminosity Sensor		
Article overview			
Article number	Luminaire	Plug	Control
9245-140	VITAWORK® 7 Asym. PIR	Schuko-plug	Dimmable plus sensors
9265-140	VITAWORK® 7 Asym. PIR KP	Kettle plug	Dimmable plus sensors
9246-140	VITAWORK® 7 Sym. DIM	Schuko-plug	Dimmable
9266-140	VITAWORK® 7 Sym. DIM KP	Kettle plug	Dimmable




TECHNICAL VIEW



LIGHT DISTRIBUTION CURVE

VITAWORK®



Free download at www.luctra.eu



LUCTRA® is a brand of
DURABLE · Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77-79 · 58636 Iserlohn
Postfach 1753 · 58634 Iserlohn
Tel.: +49 23 71 66 24 45
info@luctra.eu · www.luctra.eu